HD 6/15 G CLASSIC

Compact and mobile HD 6/15 G Classic cold water high-pressure cleaner with petrol engine and robust crankshaft pump. Ideally suited for municipalities, construction and handicraft.









Order no.

1.187-010.0

- Independent high-pressure cleaning irrespective of external power sources
- Robust crankshaft pump with ceramic pistons
- Compact, light and very mobile

_		
Technical data		
EAN code		4054278731643
Flow rate	l/h	600
Working pressure	bar / MPa	150 / 15
Max. pressure	bar / MPa	200 / 20
Drive type		Petrol
Motor type		G200FA
Number of simultaneous users		1
Portability		High
Weight (with accessories)	kg	42.5
Weight incl. packaging	kg	43.6
Dimensions (L × W × H)	mm	878 × 538 × 702

Equipment		
Spray gun		Standard
High-pressure hose	m	10
Power nozzle		
Cage protective frame		-
Crankshaft pump with ceramic pistons		•
Included in the scope of supply.		





Independence

- Allows independence of external power sources.
- Complies with the requirements of exhaust emissions standard EU STAGE V.
- Convenient manual pull start.



Outstanding mobility

- Large wheels with pneumatic tyres for uneven
- The compact and slim machine is also very easy to manoeuvre in confined areas.
- For excellent mobility, comfortable transport and space-saving storage - fits perfectly in a standard car.



Durable and robust

- A robust tubular steel frame reliably protects the machine against damage.
- Thermostat valve to protect the pump from overheating in recirculation mode.
- Crankshaft pump with ceramic pistons.





























				\top
		Order no.	Description	
TRIGGER GUNS				
Spray guns				
Standard trigger gun	1	9.751-139.0	High-pressure gun for machines of the HD Classic range. With adapter for high-pressure hoses M 22×1.5 .	-
EASY!Force Advanced	2	4.118-005.0	Effortless, not energy-sapping: the EASY!Force high-pressure gun uses the recoil force of the high-pressure jet to reduce the holding force for the operator to zero.	
EASY!Force conversion kit 2 - from machine	3	4.111-051.0	Developed for retrofitting existing high-pressure cleaners from Kärcher: EASY!Force conversion kit 2 with EASY!Force high-pressure gun, spray lance, high-pressure hose and necessary adapters.	
SPRAY LANCES				
Spray lance				
600 mm spray lance	4	9.751-140.0	600 mm long, zinc coated spray lance with hand screw connection. Not rotatable.	
250 mm lance, non-rotatable	5	4.760-667.0	250 mm stainless steel lance. With manual coupling. Non-rotatable.	
Rotating spray lances				
Spray lance, 600 mm, rotatable	6	4.760-664.0	600 mm stainless steel lance (manual coupling) with ergonomic handle for ease of use and protection. Rotatable 360° under pressure.	
Spray lance, 840 mm, rotatable	7	4.760-663.0	850 mm stainless steel lance (manual coupling) with ergonomic handle for ease of use and protection. Rotatable 360° under pressure.	
Spray lance, 1050 mm, rotatable	8	4.760-660.0	1050 mm stainless steel lance (manual coupling) with ergonomic handle for ease of use and protection. Rotatable 360° under pressure.	
Spray lance, 1550 mm, rotatable	9	4.760-661.0	1550 mm stainless steel lance (manual coupling) with ergonomic handle for ease of use and protection. Rotatable 360° under pressure.	
Spray lance, 2050 mm, rotatable	10	4.760-662.0	2050 mm stainless steel lance (manual coupling) with ergonomic handle for ease of use and protection. Rotatable 360° under pressure.	
Angular spray lance		•		
Spray lance for toilets and rain gutters	11	4.760-073.0	Stainless steel lance WC and gutter with nozzle insert. Specially shaped for effective and hygienic cleaning of gutters and toilets.	
Flexible spray lance		•		
Flexible lance, 1050 mm	12	6.394-654.0	1050 mm flexible lance with variable bend from 20° to 140° , ideal for cleaning difficult to reach areas, e.g. gutters.	
High pressure articulated joint	13	4.481-039.0	High-pressure articulated joint: Thanks to infinite angle adjustment up to 120°, this tool is ideal to effortlessly clean hard-to-reach areas. Simply attach to the spray lance of the pressure washer.	
Undercarriage spray lance				
Underbody lance	14	4.760-245.0	Stainless steel lance for effective and easy underbody and wheel arch cleaning. Without high-pressure nozzle.	

lacksquare Included in the scope of supply. \Box Available accessories.

























		Order no.	Description	
KÄRCHER POWER NOZZLE				
Power nozzle spray angle 25°				
Power nozzle 25°, 035	15	2.885-255.0	Flat stream for large area performance and stubborn dirt.	
ROTARY NOZZLES (DIRT BLASTERS)				
Dirt blaster, large				
Dirt blaster, 040	16	4.763-252.0	The dirt blaster with rotating pencil jet offers 10 times better cleaning performance. Ceramic nozzland bearing ring for a long service life. Further data: Max. 300 bar, 30 MPa, 85°C.	e [
HIGH-PRESSURE HOSES				
Standard with unions on both sides				
High-pressure hose, 10 m, DN 8, 315 bar, $2 \times M22 \times 1.5$	17	6.391-342.0	To extend the operating radius with the high-pressure cleaner. Connection on both sides M22 × 1.5	i. 🗆
High-pressure hose, 15 m, DN 8, 315 bar, 2 × M22 × 1.5	18	6.390-010.0	With screw connections on both sides, M 22 × 1.5 with bend protection.	
High-pressure hose, 20 m, DN 8, 315 bar, 2 × M22 × 1.5	19	6.390-031.0	Screw connections at both ends, M 22 × 1.5, with kink protection.	
High-pressure hose, 30 m, DN 8, 315 bar, 2 × M22 × 1.5	20	6.390-293.0	To extend the operating radius with the high-pressure cleaner. Connection on both sides M22 $ imes$ 1.5	i. [
Longlife 400 with unions on both sides				
High-pressure hose Longlife, 1,5 m, DN 8, 400 bar, $2 \times M22 \times 1.5$	21	6.390-178.0	1.5 m high-pressure hose (DN 8, M 22×1.5) with kink protection and connectors at both ends. For connecting to hose reels with appropriate connector (M 22×1.5).	
High-pressure hose Longlife, 10 m, DN 8, 400 bar, $2 \times M22 \times 1.5$	22	6.388-083.0	10 m high-pressure hose Longlife 400 (DN 8) with rotary coupling, two layer high-strength steel wire reinforced. Connectors at both ends. M 22 × 1.5, with kink protection.	
	23	6.391-354.0	To extend the operating radius with the high-pressure cleaner. Connection on both sides M22 $ imes$ 1.5). E
High-pressure hose Longlife, 15 m, DN 8, 400 bar, $2 \times M22 \times 1.5$	24	6.389-709.0	With rotary coupling, 2 × M 22 × 1.5	
High-pressure hose Longlife, 20 m, DN 8, 400 bar, $2 \times M22 \times 1.5$	25	6.390-027.0	with rotary coupling, 2 × M 22 × 1.5	
High-pressure hose Longlife, 30 m, DN 8, 400 bar, $2 \times M22 \times 1.5$	26	6.390-294.0	With rotary coupling, 2 × M 22 × 1.5	
Longlife food design with screw connections at	both	ends		
High-pressure hose food grade, 10 m, DN 8, 400 bar, 2 × M22 × 1.5	27	6.391-864.0	Longlife HP hose for use in the food industry. Außendecke## animal-grease-resistant, non-colour-bleeding material. With rotary coupling, 2 × M 22 × 1,5	
High-pressure hose food grade, 20 m, DN 8, 400 bar, $2 \times M22 \times 1.5$	28	6.391-887.0		

 $[\]blacksquare$ Included in the scope of supply. \qed Available accessories.





















				_
		Order no.	Description	
HIGH-PRESSURE HOSES				
Special hoses				
High-pressure hose curved, 1.5 m, DN 8, 400 bar, $1 \times M22 \times 1.5 / 1 \times AVS$ -hose reel connection	29	6.388-886.0	Connection hose in longlife quality with 2x M22 × 1.5, with angled connection on one side.	
PIPE CLEANING				
Pipe cleaning hose, ID 6				
Pipe cleaning hose, ID 6, 10 m, max. 250 bar	30	6.110-046.0	The 10 m pipe cleaning hose is a highly flexible high pressure hose for pipe interior cleaning (threaded connection for nozzle R 1/8).	
Pipe cleaning hose, DN 6, 20 m, max. 120 bar	31	6.390-028.0	The 20 m pipe cleaning hose is a highly flexible high pressure hose for pipe interior cleaning	
Pipe cleaning hose, ID 6, 20 m, max. 250 bar	32	6.110-008.0	10-008.0 (threaded connection for nozzle R 1/8).	
Pipe cleaning hose, DN 6, 30 m, max. 120 bar	33	6.390-029.0	30 m flexible high-pressure hose (DN 6) for cleaning pipes (threaded connection for R 1/8 nozzle).	
Pipe cleaning hose, ID 6, 30 m, max. 250 bar	34	6.110-047.0	The 30 m pipe cleaning hose is a highly flexible high pressure hose for pipe interior cleaning (threaded connection for nozzle R 1/8).	
Pipe cleaning hose, DN 6, 20 m, max. 250 bar	35	6.390-030.0	The 20 m pipe cleaning hose is a highly flexible high pressure hose for pipe interior cleaning (threaded connection for nozzle R 1/8).	
Pipe cleaning nozzle				
Pipe cleaning dirt blaster D21/040	36	4.765-001.0	The forward-tilted rotating pencil jet removes the most stubborn dirt. The three backwards-tilted	
Pipe cleaning dirt blaster D30/040	37	4.765-004.0	jets ensure the necessary forward movement, as well as convenient handling.	
FLOOR AND HARD SURFACE CLEANER				
Hard Surface Cleaner FRV 30				
FRV 30 surface cleaner	38	2.642-999.0	With the integrated and automatic suction of the dirty water, the FRV 30 makes surface cleaning even more efficient. There is no longer a need to rinse the surface after cleaning, as the dirty water can be removed through the 5m suction hose, which is supplied. Additional features include the non-marking steering rollers and double ceramic bearings. Machine specific nozzle kit must be ordered separately.	r
Rubber lip for FRV 30	39	2.642-910.0	For smooth floors indoors. The squeegee increases the suction performance of the FRV 30 and minimises the amount of water remaining. This means the floor is dry in just a few minutes.	
Extension hose 5 m	40	4.440-939.0	5m extension hose for FRV 30. Connection sleeve included.	
Hose fastening attachment kit	41	2.642-528.0	Suction cup for fixing the suction hose to smooth surfaces.	Г
Dirt trap attachment kit	42	2.642-532.0	Galvanised steel bucket for collecting coarse dirt and for fixing the suction hose in outside areas.	Г

 $[\]hfill\square$ Available accessories. \hfill O Detergents.

HD 6/15 G Classic, 1.187-010.0, 2023-01-22































	_			_	
		Order no.	Description		
FLOOR AND HARD SURFACE CLEANER					
Hard surface cleaner FR 30				,	
Surface Cleaner FR 30	43	2.642-997.0	Up to 10 times greater area coverage compared with the conventional high pressure jet. Plastic casing for optimal manoeuvrability, double ceramic bearing for long working times, flexible connection joint for ergonomic handling and integrated parking position. Machine specific nozzle kit must be ordered separately.		
FR 30 Me surface cleaner					
Hard surface cleaner FR 30 Me	44	2.640-355.0	Hot water resistant stainless steel surface cleaner with double ceramic bearings, non-marking swivel castors and suction hose connection. Ideal for indoor cleaning, e.g. food industry.		
Hard Surface Cleaner FR 50					
Hard surface cleaner FR 50	45	2.640-679.0	Hot water resistant stainless steel surface cleaner with 500 mm working width. Ideal for large areas.With double ceramic bearings, push handle, non-marking swivel castors and detergent dosing system.	g	
Machine-specific nozzle kits for FR	•			•	
Nozzle kit for FR, 500 l/h - 650 l/h	46	2.640-401.0	Nozzle kit includes power nozzles and unions. For Kärcher surface cleaners (500 to 650 l/h).		
Machine-specific nozzle kits for FRV					
Nozzle kit for FRV, 040	47	2.642-431.0	Machine-specific nozzle kit Kärcher power nozzles and jet nozzle for FRV 30.		
FRV 30 Me surface cleaner					
FRV 30 Me	48	2.642-911.0	Thanks to automatic suction of the dirty water, the stainless steel FRV 30 Me Surface Cleaner makes surface cleaning more efficient in both inside and outside areas. Hot water cleaning up to 85°C.		
Extension hose FRV 30 Me and FRV 50 Me	49	4.441-040.0	5 m extension hose for FRV 30 Me. Includes connecting adapter.		
FOAM SYSTEMS					
Cup foam lance					
Cup foam lance Advanced	50	6.394-969.0	Short, handy foam lance with adjustable spray angle with 1 litre detergent tank. Ideal for cleaning cars due to its compact design.		
Inno Foam Kit					
Inno Foam Set with detergent injector	51	2.640-151.0	High-pressure foam system with double lance (foam nozzle and high-pressure jet for rinsing). For use with mobile and stationary high-pressure and HDS pressure cleaners for cleaning or disinfection.		
Easy Foam Set					
Easy Foam Set with RM injector	52	2.640-691.0	HP foam system for use with. HD/HDS units for cleaning and disinfecting. Foam nozzle for connection to lance and HP chemical injector with precision 0-5% metering valve. The machine specific nozzle kit has to be ordered separately.		
Nozzle kits for Inno/Easy Foam Set					
Nozzle kit 055 for Inno / Easy Set 500-600 I/h	53	2.640-870.0	Optimal adaptation to different machine outputs for economic use.		
MIXERS AND INJECTORS					
Cleaning agent injector					
Cleaning agent injector for high pressure (without nozzle)	54	3.637-170.0	Cleaning agent dosage at high pressure 3 - 5 %		
Cleaning agent injector for high and low pressure (without nozzles)	55	3.637-001.0	Detergent injector for independent high and low pressure dosage. Maximum dosage about 15%.		
Machine-specific nozzle kit with order no. 4.6	37-033	3.0			





























		Order no.	Description	
MIXERS AND INJECTORS		Order no.	Description .	_
Machine-specific nozzle kit with order no. 4.63	37-033	3.0		
Nozzle kit HD 500-700 l/h	57	4.769-045.0	For HD 500 - 700 l/h. Consists of nozzle insert + HP power nozzle + union	
Nozzle insert with order no. 4.637-032.0				
Nozzle insert up to 1,100 l/h - high pressure	58	4.769-003.0	Nozzle insert for detergent injector 3.637-001 for high-pressure detergent application. For high-pressure cleaners with a water flow rate up to 1100 l/h.	
Nozzle insert up to 1,100 l/h - low pressure	59	4.769-001.0	For low pressure with machines up to 1.100 l/h	
QUICK CONNECT				
Quick coupling	60	6.401-458.0	For fast changes between different spray lances/accessories. Perfect for Kärcher spray unit, suitable for trigger gun/spray lance interface. With M 22 × 1.5 internal thread.	
Male coupling	61	6.401-459.0	Hardened stainless steel male coupling for quick coupling 6.401-458. With M 22×1.5 external thread.	
DRUM AND TANK CLEANING				
Add-on kit mud sucker	62	2.641-798.0	For connection to the high-pressure hose of Kärcher high-pressure cleaners: Powerful sludge suction cleaner for the retrofitting of high-pressure cleaners to dirt pumps.	
COUPLING PARTS				
Rotary coupling				
Rotary coupling	63	4.401-091.0	Reliably prevents twisting of HP hoses. Connection M 22 × 1.5 m. Handle protection	
Coupling				
Coupler -2 × M22 × 1,5	64	4.403-002.0	For connecting and extending high-pressure hoses. Connection 2 × M 22 × 1.5.	
Connector				
Nozzle screws / screw socket	65	4.402-022.0	Nozzle connector/screw connector for connecting high-pressure nozzles and accessories to the high-pressure trigger gun (with nozzle connector). Connectors: $1\times M$ 22×1.5 and $1\times M$ 18×1.5 .	
Adapters				
Sealing cone complete	66	4.424-004.0	In order to install high-pressure hose with male coupling on thread with M22 \times 1.5 Alternative:4.111-032.0 Adapter 4 – Device new / Hose old Swivel	
EASY!Lock adapter	•			
Adapter 1 M22AG-TR22AG	67	4.111-029.0	Adapter 1 to connect the old hose with the new hose	
Adapter 2 M22IG-TR22AG	68	4.111-030.0	Adapter 2 to connect the old device with the new hose and the old gun with the new hose	
Adapter 3 M22IG-TR22AG	69	4.111-031.0	Adapter 3 to connect the old gun with the new spray lance and new servo regulator	
Adapter 5 TR22IG-M22AG	70	4.111-033.0	Adapter 5 to connect the new gun with the old spray lance and new servo regulator with the old	

[☐] Available accessories.

KÄRCHER























		Order no.	Description
COUPLING PARTS			
EASY!Lock adapter			
Adapter 6 TR22IG-M22AG	71	4.111-034.0	Adapter 6 to connect the new device with the old hose and the old hose with the new gun
Adapter 7 M18IG-TR20AG	72	4.111-035.0	Adapter 7 to connect the old spray lance with the new nozzle
Adapter 8 TR20IG-M18AG	73	4.111-036.0	Adapter 8 to connect the new spray lance with the old nozzle
HOSE REELS			
Automatic, self-winding hose reels for wall mo	untin	g	
Automatic stainless steel hose reel, 20 m	74	6.391-520.0	
Automatic stainless steel hose reel, 40 m	75	6.392-442.0	Automatic hose reels provide the highest level of safety and convenience for winding and unwinding HP hoses. Compatible high-pressure hose, e.g. order no. 6.110-076.0 (ID 8, 40 m, 400 bar, 1x hose reel connection attachment kit).
Powder-coated swivel holder	76	2.639-931.0	Swivel holder for automatic hose reel wall mounting. For maximum action radius and flexibility of high-pressure hose. Rotatable 120°. Galvanised steel.
Stainless steel swivel holder	77	2.641-867.0	Swivelling wall bracket made of high-grade steel (for 2.641-866). This makes maximum flexibility and convenience possible when working with the HP hose.
WET BLASTING ATTACHMENT			
Wet blasting attachment (without nozzle)			
Wet blasting attachment with flow control (without nozzles)	78	4.762-010.0	Paint, rust and scale removal made easy: Kärcher wet blasting attachment with flow control for adding blasting abrasive to the high-pressure jet.
Wet blasting attachment without flow control (nozzles not included)	79	4.762-022.0	Addition of spray agent to the high pressure jet. For paint stripping, rust removal and descaling. Assembly on spray lance instead of high-pressure nozzle.Without water flow regulation
Nozzle kits for wet jet unit			
Nozzle kit for wet jet unit 040	80	2.112-019.0	Nozzle kit with wet blasting nozzle and nozzle insert (type specific). For optimal Kärcher wet blasting attachment performance. Only in combination with wet blasting attachment 4.115-000.0 4.115-006.0.
	81	2.637-900.0	Nozzle kit with wet blasting nozzle and nozzle insert (type specific). For optimal Kärcher wet blasting attachment performance. Only in combination with wet blasting attachment 4.762-010/-022.
Boron carbide nozzle			
Boron carbide nozzle, for machines up to 1,000 l/h	82	6.415-084.0	In addition to nozzle packs. Very wear-resistant nozzle with boron carbide chuck for continuous-duty operation.
WATER CONNECTION			
Geka coupling			
Geka connector with hose barb, R 3/4"	83	6.388-455.0	with hose liner
Suction filter			
Water suction filter	84	6.414-956.0	Suitable for ponds, storage tanks or similar, polyamide filter casing, stainless steel strainer, 800 µm

 $[\]hfill \square$ Available accessories.



















	_			_
		Order no.	Description	
WATER CONNECTION	<u>'</u>			
Suction filter				
Suction filter with check valve	85	4.730-012.0	Brass suction filter suitable for ponds, storage tanks, etc. With check valve.	
Water fine filter				
Universal water fine filter, 25 µm	86	2.637-020.0	Water fine filter, mesh size 25 µm, max. temperature 50 °C. Protects the machine from small dirt particles in the water. Water volume up to 1200 l/h. 3/4" connection, with 1" adapter.	
Water fine filter, with adapter	87	4.730-102.0	Fine-mesh water filter, 125 μ m, max. temperature 50°C. Protects the high-pressure cleaner from dirt particles contained in the water. Water flow rate up to 1200 l/h. Connection 3/4", with adapter 1".	r,
Water supply hose		'		
Water supply hose	88	4.440-038.0	NW 13 R1" / R 3/4", up to 30 °C	
	89	4.440-207.0	NW 19 R1" / R 3/4", up to 85 °C, for pick-up	
Backflow check valve				
Backflow preventer	90	2.641-374.0	To prevent detergent getting into the drinking water cycle in case of inlet at low-pressure. - hot water resistant up to 80 °C - tested according to IEC 60335-2-79 - integrated leakage protection	
WASHING BRUSHES				+
Push-on washing brush				
Push-on wash brush	91	4.762-016.0	For general-purpose cleaning of all surfaces. Clamps directly onto the spray lance. Connection M 18×1.5	
	92	4.113-001.0	For universal use for surface cleaning. Mounted using clamp directly at the spray lance. TR thread connection	
Rotating washing brush		·		
Rotating wash brush for < 800 l/h machines, nylon bristles	93	4.762-561.0	The rotating wash brush gently removes fine dust and traffic film from all surfaces. Temperature resistant up to 60° C. (M 18×1.5 , replaceable brush insert).	
Rotating wash brush for < 800 l/h machines, natural bristles	94	4.762-560.0	Driven by water stream. Gently removes fine dust and traffic film from any surface. Temperature resistant up to 60° C, M 18×1.5 (replaceable brush insert).	

[☐] Available accessories.